



Suitable for making service connections, fixing valves and fittings. It is possible to supply an extensive range of outlets, for instance, BSP, BSO and BSD outlets. Available in one, two and three sections.

- Available outlets: BSP: 1/2" · 3/4" · 1" · 1 1/4" · 1 1/2" · 2" · 2 1/2" · 3" · 4"  
 BSO: 2 1/2" · 3"  
 BSD: 2"int. / 2 1/2" ext.  
 Polsafe: 1 1/2" · 2"

### SPECIFICATIONS:

- Thread protection caps** - Plastic caps to protect the thread.
- Bolts** - Stainless steel AISI 304 (A2); Dimensions depend on diameter. M12, M14 or M16 (metric thread according DIN267). Thread is PTFE (Teflon™) coated to prevent galling.
- Lifterbar** - Stainless steel AISI 304 (A2). L shaped. Lips hold bolts in position while tightening.
- Nuts** - Stainless steel AISI 304 (A2). Size M12, M14 or M16 according DIN934. Extra yellow passivated to optimize free running.
- Body Shell** - Stainless steel AISI 304 (A2).
- Armour plate** - Vulcanised into the gasket for all standard clamps. Stainless steel AISI 304.
- Gasket** - NBR gasket, proper for both gas and water purposes. It has a waffle structure and tapered ends. EPDM gasket is optional.
- Sidebar** - Stainless steel AISI 304.
- Guide finger** - Stainless steel AISI 304, Guide fingers keep the bolts in position.
- Outlets** - BSP, BPD, BSO and Polsafe.
- Additional** - After welding all stainless steel parts are passivated to obtain a high corrosion resistance. Further to the above mentioned technical specifications; products are also available in AISI 316/316L quality.

### Minimal dimensions with outlets:

Outlet	Single band	Length	Double Band	Length
1/2"	40 - 44	150	88-110	200
3/4"	48 - 52	150	88-110	200
1"	57 - 64	150	88-110	200
1 1/4"	67 - 74	150	88-110	200
1 1/2"	70 - 77	200	88-110	200
2"	87 - 95	200	88-110	200
2 1/2"	-	-	108-128	200
3"	-	-	130-150	300
4"	-	-	159-170	400

All mentioned working pressures on all our documents are only valid in optimum circumstances and based on document 2009.04.24.PRES-N002. please contact us for a copy of this document.

Tracon International BV reserves the right to vary specifications or delete models from the range without prior notice. Tracon International BV takes no responsibility for printing errors.