

TECHNICAL DATASHEET




EF REDUCER

01 Update - 12/2018

TECHNICAL DATA

Article No	101 117 2080 0111
d1 (mm)	110
d2 (mm)	90
D1 (mm)	134
D2 (mm)	111
le1 (mm)	71
le2 (mm)	63
Z (mm)	138
Weight (Kg)	0.535
Box Quantity (pcs)	20
Box Dimension (cm)	31x50x45

INJECTION MOULDED



IDENTIFICATION OF PRODUCT

D(mm)	110-90
SDR	11
RAW MATERIAL	PE 100
PRESSURE CLASS	16 Bar Water 10 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3 EN 1555-3 AS / NZS 4129
SPECIFICATION	Suitable for SDR11....17 pipe 4 mm pin connectors

EF SPECIFICATION

WELDING VOLTAGE	40V
RESISTANCE	1.14 Ω
WELDING TIME	120 Sec
COOLING TIME	10 Min
WINDING TYPE	Monofilar
WELDING BARCODE	



Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance $\pm 5\%$. NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.