# TECHNICAL DATASHEET



## **EF COUPLER**


00 Update - 09/2015

### TECHNICAL DATA

Article No	001 117 2160 0125
<b>d</b> (mm)	125
<b>D</b> (mm)	151
Z (mm)	154
<b>m</b> (mm)	37
<b>Weight</b> (Kg)	0,77
Box Quantity (pcs)	15
Box Dimension (cm)	36x40x51

### **INJECTION MOULDED**





#### **IDENTIFICATION OF PRODUCT**

D(mm)	125
SDR	11
RAW MATERIAL	PE 100
PRESSURE CLASS	16 Bar Water 10 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3
	EN 1555-3
	AS / NZS 4129
SPECIFICATION	Suitable for SDR1117 pipe
	Removable center stopper

4 mm pin connectors

### **EF SPECIFICATION**

40 V
1.15 Ω
270 Sec
15 Min
Monofilar
442007321253401156270113

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance  $\pm$  5%. NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.