

TECHNICAL DATASHEET




EF TAPPING SADDLE

00 Update - 09/2015

TECHNICAL DATA

Article No	001 117 2071 0145
d (mm)	140
d1 (mm)	63
le (mm)	100
h (mm)	238
h1 (mm)	95
Z (mm)	182
Weight (Kg)	0,98
Box Quantity (pcs)	6
Box Dimension (cm)	55x30x38


INJECTION MOULDED



IDENTIFICATION OF PRODUCT

D(mm)	140-63
SDR	11
RAW MATERIAL	PE 100
PRESSURE CLASS	16 Bar Water 10 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3

EF SPECIFICATION

WELDING VOLTAGE	40 V
RESISTANCE	7,3 Ω
WELDING TIME	150 Sec
COOLING TIME	15 Min
WINDING TYPE	Monofilar
WELDING BARCODE	

941420323153407305150114

SPECIFICATION	Suitable for SDR11.....17 pipe Injected monobloc type 4 mm pin connectors Long Fusion outlet Hexagon wrench 12 mm O-ring sealed screw cap
---------------	--

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance \pm 5%. NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.