TECHNICAL DATASHEET



EF COUPLER


01 Update - 02/2020

TECHNICAL DATA

Article No	001 117 2160 0160
d (mm)	160
D (mm)	193
Z (mm)	172
m (mm)	42
Weight (Kg)	1,33
Box Quantity (pcs)	8
Box Dimension (cm)	55x60x21

INJECTION MOULDED





IDENTIFICATION OF PRODUCT

D(mm)	160
SDR	11
RAW MATERIAL	PE 100
PRESSURE CLASS	16 Bar Water 10 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3
	EN 1555-3
	AS / NZS 4129
SPECIFICATION	Suitable for SDR1117 pipe
	Removable center stopper

4 mm pin connectors

EF SPECIFICATION

WELDING VOLTAGE	40 V
RESISTANCE	0.91 Ω
WELDING TIME	360 Sec
COOLING TIME	20 Min
WINDING TYPE	Monofilar
WELDING BARCODE	442007331603400916360118

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance ± 5%. NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.