

# TECHNICAL DATASHEET




## EF TAPPING SADDLE

01 Update - 02/2018

### TECHNICAL DATA

Article No	001 117 2071 0234
d (mm)	225
d1 (mm)	63
le (mm)	100
h (mm)	281
h1 (mm)	137
Z (mm)	195
Weight (Kg)	1,16
Box Quantity (pcs)	4
Box Dimension (cm)	55x30x38


### INJECTION MOULDED



### IDENTIFICATION OF PRODUCT

D(mm)	225-63
SDR	11
RAW MATERIAL	PE 100
PRESSURE CLASS	16 Bar Water 10 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3

### EF SPECIFICATION

WELDING VOLTAGE	40 V
RESISTANCE	7,3 $\Omega$
WELDING TIME	130 Sec
COOLING TIME	15 Min
WINDING TYPE	Monofilar
WELDING BARCODE	

142007324343407305130118

### SPECIFICATION

Suitable for SDR11.....17 pipe  
Injected monobloc type  
4 mm pin connectors  
Long Fusion outlet  
Hexagon wrench 12 mm  
O-ring sealed screw cap

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance  $\pm$  5%. NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.