TECHNICAL DATASHEET



00 Update - 09/2015

EF COUPLER


TECHNICAL DATA

INJECTION N	IOULDED
--------------------	---------

Article No	001 117 2160 0280
d (mm)	280
D (mm)	340
Z (mm)	244
m (mm)	52
Weight (Kg)	6,08
Box Quantity (pcs)	1
Box Dimension	36x36x28

IDENTIFICATION OF PRODUCT





EF SPECIFICATION

D(mm)	280
SDR	11
RAW MATERIAL	PE 100
PRESSURE CLASS	16 Bar Water 10 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3
	EN 1555-3
	AS / NZS 4129
SPECIFICATION	Suitable for SDR1117 pipe
	Removable center stopper
	4 mm pin connectors

WELDING VOLTAGE	40 V
RESISTANCE	0.65 Ω
WELDING TIME	800 Sec
COOLING TIME	30 Min
WINDING TYPE	Monofilar
WELDING BARCODE	442007342803400656800114

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance \pm 5%. NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.