# TECHNICAL DATASHEET



## **EF COUPLER**


01 Update - 11/2016

### TECHNICAL DATA

Article No	101 117 2160 0040
<b>d</b> (mm)	40
<b>D</b> (mm)	52
<b>Z</b> (mm)	90
<b>m</b> (mm)	19
<b>Weight</b> (Kg)	0,08
Box Quantity (pcs)	90
Box Dimension (cm)	31x50x36

### **INJECTION MOULDED**





### **IDENTIFICATION OF PRODUCT**

D(mm)	40
SDR	11
RAW MATERIAL	PE 100
PRESSURE CLASS	16 Bar Water 10 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3
	EN 1555-3
	AS / NZS 4129
SPECIFICATION	Suitable for SDR11 pipe
	Removable center stopper

4 mm pin connectors

#### **EF SPECIFICATION**

WELDING VOLTAGE	40 V
RESISTANCE	2.02 Ω
WELDING TIME	40 Sec
COOLING TIME	5 Min
WINDING TYPE	Monofilar
WELDING BARCODE	951420300403992025040118 -

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance  $\pm$  5%. NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.