



Certificate number: 2410772 (1)

Issued 30/10/2024

Expires 30/10/2029

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

IVR S.p.A.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:

IVR S.p.A
Via Brughiera III
1 - Loc. Piano Rosa
28010
Boca (NO)
Italy



KUKreg4

Product Certificate

Appendix to Certificate number: 2410772

The following products belong to this certificate

PRODUCT DESCRIPTION EXPORT range of lever operated or butterfly handle spherical valves with chromium plated brass bodies, chromium plated brass balls and PTFE seals. ATS3 – Without Production Surveillance.
MODEL(S) IVR 45 Full bore ball valve threaded ends F/F - BSP Threads 1/4" - 3/8" - 1/2" - 3/4" PN50 1" - 1 1/4" PN40 1 1/2" - 2" PN32 2" 1/2" - 3" - 4" PN 25 IVR 46 Full bore ball valve threaded ends M/F – BSP Threads 1/4" - 3/8" - 1/2" - 3/4" PN50 1" - 1 1/4" PN40 1 1/2" - 2" PN32 IVR 47 Full bore ball valve threaded ends M/M - BSP Threads 1/2" - 3/4" PN50 1" PN40 The version standard has the handle regular; The version "PLUS" has the handle bigger; The version "LB" has the handle blue; The version "/A" has red butterfly handle; The version "LD" has lockable handle
SIZE: See models.
SCOPE: Manufacturer recommended maximum working pressure see model & maximum operating temperature 23°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 23°C.
MARKING company logo, DN, PN, size, Date of manufacture (MM-YY) moulded on body; company logo, on, off printed on handle.
MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES N/A.
ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.

Extra Notes