



„K-Fiberclima Pipe PN 16“ SDR 11 – S 5 (20° C/1,6 MPa – 70° C/0,8 MPa), length 4 meter

  Material: PP-RCT GF Colour: green with 4 blue stripes Standards: DIN EN ISO 15874	Code	D	DN	Di	S min.	Pack.	Weight kg/m	Water capacity l/m
	AQ160F20	20	15	14,4	2,8*	100	0,16	0,16
	AQ160F25	25	20	18,0	3,5*	100	0,25	0,25
	AQ160F32	32	25	26,2	2,9	60	0,28	0,54
	AQ160F40	40	32	32,6	3,7	40	0,43	0,83
	AQ160F50	50	40	40,8	4,6	20	0,67	1,31
	AQ160F63	63	50	51,4	5,8	20	1,04	2,07
	AQ160F75	75	-	61,4	6,8	8	1,44	2,96
	AQ160F90	90	65	73,6	8,2	8	2,08	4,25
	AQ160F110	110	80	90,0	10,0	8	3,10	6,36
	AQ160F125	125	100	102,2	11,4	4	4,02	8,20
	AQ160F160	160	125	130,8	14,6	4	6,50	13,43
	AQ160F200	200	160	163,6	18,2	4	10,09	21,01
	AQ160F250	250	200	204,6	22,7	4	15,01	32,86

* SDR 7,4 - S 3,2

„K-Fiber Pipe PN 20“ SDR 7,4 – S 3,2 (20° C/2,0 MPa – 70° C/1,0 MPa), length 4 meter

  Material: PP-RCT GF Colour: green with 4 red stripes Standards: DIN EN ISO 15874	Code	D	DN	Di	S min.	Pack.	Weight kg/m	Water capacity l/m
	AQ200F20	20	15	14,4	2,8	100	0,16	0,16
	AQ200F25	25	20	18,0	3,5	100	0,25	0,25
	AQ200F32	32	25	23,2	4,4	60	0,39	0,42
	AQ200F40	40	32	29,0	5,5	40	0,59	0,66
	AQ200F50	50	40	36,2	6,9	20	0,91	1,03
	AQ200F63	63	50	45,8	8,6	20	1,45	1,63
	AQ200F75	75	-	54,4	10,3	8	2,06	2,31
	AQ200F90	90	65	65,4	12,3	8	2,94	3,32
	AQ200F110	110	80	79,8	15,1	8	4,36	4,97
	AQ200F125	125	100	90,8	17,1	4	5,61	6,47
	AQ200F160	160	125	116,2	21,9	4	9,09	10,60
	AQ200F200	200	160	145,2	27,4	4	14,23	16,55
	AQ200F250	250	200	181,6	34,2	4	22,08	25,89